

RETI ELETTROSALDATE STANDARD

INFORMAZIONI TECNICHE

TIPO	Ø FILO mm		MAGLIA cm		DIM. PANN. cm		Sup. pann. m ²	Peso pann. kg	Peso m ² kg	LEGACCIO		
	long.	trasv.	long.	trasv.	long.	trasv.				N° pann. per leg.	Altezza cm	Peso kg
510	5	5	10	10	200	300	6,00	18,48	3,08	100	55	1848
510	5	5	10	10	225	400	9,00	28,03	3,08	50	28	1402
515	5	5	15	15	200	300	6,00	12,63	2,11	100	55	1263
515	5	5	15	15	225	400	9,00	18,60	2,06	100	55	1860
520	5	5	20	20	200	300	6,00	9,24	1,54	100	55	924
520	5	5	20	20	225	400	9,00	14,32	1,59	100	55	1432
610	6	6	10	10	200	300	6,00	26,64	4,44	50	32	1332
610	6	6	10	10	225	400	9,00	40,40	4,44	50	32	2020
615	6	6	15	15	200	300	6,00	18,20	3,03	80	53	1456
615	6	6	15	15	225	400	9,00	26,81	2,96	50	32	1341
620	6	6	20	20	200	300	6,00	13,32	2,22	80	53	1066
620	6	6	20	20	225	400	9,00	20,65	2,29	80	53	1652
815	8	8	15	15	200	300	6,00	32,39	5,40	50	44	1620
815	8	8	15	15	225	400	9,00	47,70	5,26	25	22	1193
820	8	8	20	20	200	300	6,00	23,70	3,95	50	44	1185
820	8	8	20	20	225	400	9,00	36,70	4,08	50	44	1837
830	8	8	30	30	200	270	5,40	14,85	2,70	50	44	729
1020	10	10	20	20	225	400	9,00	57,38	6,38	25	27	1435
1220	12	12	20	20	225	400	9,00	82,58	9,18	25	33	2065

RETE PER PARETE

setto1/1	8	6	30	15	230	285	6,55	18,71	2,85	50	36,5	935
setto1/C*	8	6	30	15	230	350	8,05	20,76	2,58	50	36,5	1038

*Pannelli con riprese da 70 cm

